







DIAMETRO					Carga de trabajo en kilos			Carga de trabajo en kilos		
					2 RAMALES			3 Y 4 RAMALES		
Inch	Mm	VERTICAL	LAZO	U	 60°	 45°	 30°	 60°	 45°	 30°
1/4"	6,35	500	400	1.000	850	700	500	1.300	1.050	750
5/16"	8	700	560	1.400	1.190	980	700	1.820	1.470	1.050
3/8"	9,5	1.000	800	2.000	1.700	1.400	1.000	2.600	2.100	1.500
7/16"	11	1.500	1.200	3.000	2.550	2.100	1.500	3.900	3.150	2.250
1/2"	12,7	2.170	1.628	4.340	3.689	3.038	2.170	5.642	4.557	3.255
9/16"	14,28	2.500	2.000	5.000	4.250	3.500	2.500	6.500	5.250	3.750
5/8"	15,87	3.000	2.400	6.000	5.100	4.200	3.000	7.800	6.300	4.500
3/4"	19,05	4.500	3.600	9.000	7.650	6.300	4.500	11.700	9.450	6.750
7/8"	22,22	5.500	4.400	11.000	9.350	7.700	5.500	14.300	11.550	8.250
1"	24,5	8.500	6.800	17.000	14.450	11.900	8.500	22.100	17.850	12.750
1.1/8"	28,57	9.500	7.600	19.000	16.150	13.300	9.500	24.700	19.950	14.250
1.1/4"	31,75	12.000	9.600	24.000	20.400	16.800	12.000	31.200	25.200	18.000
1.3/8"	34,9	14.000	11.200	28.000	23.800	19.600	14.000	36.400	29.400	21.000
1.1/2"	38,1	17.000	13.600	34.000	28.900	23.800	17.000	44.200	35.700	25.500

FACTOR DE SEGURIDAD 5 A 1

